



US006309450B1

(12) **United States Patent**
Millen et al.

(10) **Patent No.: US 6,309,450 B1**
(45) **Date of Patent: Oct. 30, 2001**

(54) **FLOW-THROUGH ADSORBENT UNIT
ASSEMBLY FOR RECEIVER DRYER**

(75) Inventors: **Peter R. Millen**, Perry, NY (US);
Stephen F. Sullivan, Boardman, OH
(US)

(73) Assignee: **Multisorb Technologies, Inc.**, Buffalo,
NY (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/692,698**

(22) Filed: **Oct. 19, 2000**

Related U.S. Application Data

(63) Continuation-in-part of application No. 09/456,669, filed on
Dec. 9, 1999, now abandoned.

(51) Int. Cl.⁷ **B01D 53/04; B01D 53/26**

(52) U.S. Cl. **96/131; 96/135; 96/137;**
96/147; 96/149; 96/151; 55/513; 55/DIG. 17;
210/282

(58) Field of Search **55/513, 515, 522,**
55/DIG. 17; 96/131-141, 147, 149, 151;
210/282

(56) References Cited

U.S. PATENT DOCUMENTS

2,758,719 * 8/1956 Line 96/147 X
3,221,478 12/1965 Norton .
3,353,339 * 11/1967 Walter 96/137
3,407,936 10/1968 Balogh .

3,799,352 3/1974 McClive .
3,815,752 6/1974 Hoffman et al. .
3,879,292 4/1975 McClive .
4,436,623 3/1984 Cullen et al. .
4,457,843 7/1984 Cullen et al. .
4,908,132 * 3/1990 Koval et al. 96/137 X
5,569,316 * 10/1996 Flaugh et al. 96/135
5,689,893 * 11/1997 Mitsch 96/137 X
5,716,432 * 2/1998 Perrine 96/135
5,718,743 2/1998 Donnelly et al. .
5,759,241 * 6/1998 Klett et al. 96/134
5,779,772 * 7/1998 Unger et al. 96/137
5,785,742 * 7/1998 Mitsch 96/151 X
5,865,998 * 2/1999 Abraham et al. 96/131 X
5,910,165 * 6/1999 Haramoto et al. 96/151 X
6,170,288 * 1/2001 Incorvia 96/135 X
6,178,772 * 1/2001 Incorvia 96/135 X

* cited by examiner

Primary Examiner—Robert H. Spitzer

(74) Attorney, Agent, or Firm—Joseph P. Gastel

(57) ABSTRACT

An adsorbent unit assembly including a holder, an elongated member on the holder, an enlarged portion at the end of the elongated member, a cylindrical adsorbent unit having an opening therein for receiving the elongated member, and a grid mounted on the elongated member on the opposite side of the adsorbent unit from the enlarged portion. The foregoing adsorbent unit assembly is mounted within the housing of a receiver dryer by compressing one or more adsorbent units on the elongated member between the grid and the enlarged portion so as to cause the outer sides of the adsorbent units to bear against the inside surface of the housing while the grid also provides an interference fit with the housing.

42 Claims, 8 Drawing Sheets

